

ZERO.B Magna⁺ Universal



FEATURES:

- 7 Stage purification with RO+UV+UF+Minera Balance
- Wall mount elegant design for modern kitchen
- Detachable 6L tank for easy cleaning

TECHNICAL SPECIFICATIONS

PARAMETERS

Purification flow rate	10 LPH*
Storage tank capacity	6 liters
% Recovery	40-50 %*
% salt rejection	90-95%
Dimensions (L X W X H)	28 x 20 x 37 (cm)

PARAMETERS

PURIFICATION STAGES

Purification	Filter bag , 5 micron filter and activated carbon
Nova Cartridge	4" cartridge
RO Purification	RO membrane
UF Purifications	4" UF module
UV Purifications	UV module

ELECTRIC SUPPLY

Operating Voltage	230+10% VAC
Power consumption(W)	30 Watts max

INLET WATER CONDITION

Inlet opening	1/2" BSP thread connection
Inlet water temperature	Less than 45 Centigrade
Inlet pressure	0.5- 2 kg/cm ²
Feed water TDS (PPM)	Up to 1500 ppm
Turbidity (NTU)	Less than 5
Total hardness(PPM)	500 max
Free chlorine(PPM)	Nil
Silica(PPM)	Less than 20
Iron and manganese(PPM)	Nil
Oil and Grease(PPM)	Nil

NOTE:- * Under standard condition of 750ppm TDS Feed water
Technical specifications are subject to change without prior notice.

Ideal for water with TDS above 300 PPM

INDICATIONS: Power ON- Red ■ | Process ON - Blue ■ | Tank Full-White ■